

Impact of the reactor bottom shape on the solid sodium borohydride hydrolysis for hydrogen generation

M.J.F. Ferreira¹, V. R. Fernandes², C.M. Rangel² and A.M.F.R. Pinto³

^{1,3}Centro de Estudos de Fenómenos de Transporte - CEFT, Departamento de Engenharia Química, Faculdade de Engenharia da Universidade do Porto, Rua Dr. Roberto Frias s/n, 4200-465 Porto, Portugal
emails: fermjf@fe.up.pt (M.J.F. Ferreira); apinto@fe.up.pt (A.M.F.R. Pinto)

²Laboratório Nacional de Energia e Geologia – LNEG, Fuel Cell and Hydrogen Unit, Estrada do Paço do Lumiar 22, 1649-038 Lisboa, Portugal
email: carmen.rangel@lneg.pt

Keywords: *sodium borohydride; hydrogen generation; nickel-based catalyst; batch reactor; reactor bottom shape*

Abstract

Sodium borohydride (NaBH₄) is a chemical hydride that produces hydrogen (H₂) ‘on-demand’ through the reaction with water, and exhibits high gravimetric hydrogen storage capacity (10.8 wt.%). NaBH₄ has been appointed as an efficient energy/hydrogen carrier for use with fuel cells [1-6]. Unfortunately, problems also exist with NaBH₄ hydrolysis: H₂ production rates are not sufficiently fast, reaction completion is not always reachable and effective gravimetric (and volumetric) H₂ storage capacity is far from the theoretical value.

The present study reports original experimental work on generation of hydrogen, by hydrolysis of solid sodium borohydride with stoichiometric amount of distilled water (H₂O/NaBH₄: 2, 3 and 4 mol/mol), in the presence of a powder unsupported Ni-Ru based catalyst, reused about 320 times. The experiments, performed in two batch reactors with equal internal volume but with different bottom shapes (flat and conical), reveal - for the conical bottom shape with any excess of water - 8.1 H₂ wt% and 92 kg H₂/m³ (materials-only basis), and a H₂ rate of 87.4 L(H₂) min⁻¹g⁻¹ catalyst. The role of reactor bottom geometry on the solid NaBH₄ hydrolysis - with any excess of water - is, as the authors are aware, for the first time here referred.

References

- [1] U.B. Demirci, O. Akdim, J. Andrieux, J. Hannauer, R. Chamoun, P. Miele “Sodium borohydride hydrolysis as hydrogen generator: issues, state of the art and applicability upstream from a fuel cell”, *Fuel Cells*, 10, 3, 2010, 335-350.
 - [2] A.M.F.R. Pinto, D.S. Falcão, R.A. Silva, C.M. Rangel “Hydrogen generation and storage from hydrolysis of sodium borohydride in batch reactors”, *Int. J. of Hydrogen Energy*, 31, 2006, 1341-1347.
 - [3] M.J.F. Ferreira, V.R. Fernandes, C.M. Rangel, L. Gales, A.M.F.R. Pinto “Successive loadings of reactant in the hydrogen generation by hydrolysis of sodium borohydride in batch reactors”, *J. N. Mater. Electrochem. Syst.*, 12, 2009, 153-159.
 - [4] M.J.F. Ferreira, L. Gales, V.R. Fernandes, C.M. Rangel, A.M.F.R. Pinto “Alkali free hydrolysis of sodium borohydride for hydrogen generation under pressure”, *Int. J. Hydrogen Energy*, 35, 2010, 9869-9878.
 - [5] M.J.F. Ferreira, V.R. Fernandes, L. Gales, C.M. Rangel, A.M.F.R. Pinto “Effects of the addition of an organic polymer on the hydrolysis of sodium tetrahydroborate in batch reactors”, *Int. J. Hydrogen Energy*, 35, 2010, 11456-11469.
 - [6] A.M.F.R. Pinto, M.J.F. Ferreira, V.R. Fernandes, C.M. Rangel “Durability and reutilization capabilities of a Ni-Ru catalyst for the hydrolysis of sodium borohydride in batch reactors”, *Catalysis Today* (2011), Vol. 170 (1), 40-49, 2011.
-