

**EFFECT OF THE OXIDE LOADING ON THE SURFACE  
CHARACTERISTICS OF LaNiO<sub>3</sub> OXIDE COATED ELECTRODES**

C.O. Soares, R.A.Silva\*, M. D. Carvalho, M.E. Melo Jorge, A. Gomes,

C.M. Rangel\*, M.I. da Silva Pereira

C.C.M.M., Departamento de Química e Bioquímica da Faculdade de Ciências da Universidade de Lisboa,  
Campo Grande, 1749-016 Lisboa, Portugal

\*Laboratório Nacional de Energia e Geologia, Paço do Lumiar 22, Fuel Cells and Hydrogen Unit,  
1649-038 Lisboa, Portugal. e-mail: [carmen.rangel@lneg.pt](mailto:carmen.rangel@lneg.pt)

---

**Keywords:** LaNiO<sub>3</sub> films. Foam nickel support. Oxide loading. Roughness factor. Morphology factor.

**Abstract**

The LaNiO<sub>3</sub> perovskite-type oxide is one of the most tested anode for the oxygen evolution reaction in alkaline solutions. It is well established that the oxide preparation conditions and the electrode fabrication are key factors to control the electrochemical behaviour of oxide coatings.

In a previous work the authors studied the influence of preparation conditions of the oxide and support type on the electrochemical behaviour of Ni foam coated LaNiO<sub>3</sub> electrodes. Ni foam was selected as support due to its unique characteristics namely low contact resistance between the oxide and support, possibility of high metal oxide loadings and dimensional stability [1]. No studies were performed, concerning the influence of the oxide loading.

Studies performed by Singh et al. on LaNiO<sub>3</sub> coatings on Ni foil supports have shown that the electrode roughness factor increased with increase in oxide loading at the beginning and finally attained a constant value around 0.03 g cm<sup>-2</sup> [2].

The present work reports on the study of the dependence of roughness factor ( $R_f$ ) and morphology factor ( $\phi$ ) on the oxide loading for Ni foam coated LaNiO<sub>3</sub> electrodes with loadings varying between 0.02 and 0.14 g cm<sup>-2</sup>. Cyclic voltammetry and electrochemical impedance spectroscopy were used to evaluate the  $R_f$  and  $\phi$  values, complemented by optical microscopy observations.

A non-linear increase of both  $R_f$  and  $\phi$  with the oxide loading is observed, showing a level off when the oxide loading is increased. The level off was interpreted as a progressive exclusion of the crystallites from the contact with the solution as the oxide coating thickness increases.

**Acknowledgements**

This work is partially financed by Fundação para a Ciência e Tecnologia (FCT), under contract n° PTDC/CTM/102545/2008. C.O. Soares acknowledges a grant from FCT under the same contract.

**References**

- [1] C.O. Soares, M. D. Carvalho, M.E. Melo Jorge, A. Gomes, R.A. Silva, C.M. Rangel, M.I. da Silva Pereira, "Improving electrocatalytic activity of LaNiO<sub>3</sub> films by deposition on foam nickel substrates" *Port. Electrochim. Acta* 2011(in press)
- [2] R.N. Singh, A.N. Jain, S.K. Tiwari, G. Poillerat, P. Chartier "Physicochemical and electrocatalytic properties of LaNiO<sub>3</sub> prepared by low-temperature route for anode application in alkaline water electrolysis", *J. Appl. Electrochem.* 25, 1995, 1133–1138.